






# High Pressure Cleaner

## HSC840-INOX 24kW



	<b>1400 U/min</b>	<b>TSS</b>
<b>TOTAL STOP</b>		
		

**INOX**

Type		HSC840-INOX 24kW
Voltage	3/N/PE/AC/50Hz/400V	<ul style="list-style-type: none"> <li>Stainless steel (food safe)</li> <li>Etronic I - Controls</li> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Water-Supply separation acc. DIN EN 1717 class 4</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Operating pressure	30-130bar/3-13MPa	
Max. pressure	150bar/15MPa	
Discharge capacity	300-720l/h	
Nozzle size	045	
Heating capacity	24kW	
Hot water capacity	30-80°C	
Pump speed	1400rpm	
Connected load	28,8kW/44,2A	
Electrical protection	3x50A slow	
Weight net/with package		264kg/281kg
Dimensions device/with package (LxWxH)		122x75,5x162,5cm/125x81,5x175,5cm

Self-supporting, robust, device-chassis made out of stainless-steel, suitable for floor installation, stainless-steel hotwater-boiler with 65l capacity with pre-heating and buffer storage for immediate hot-water use and hot-water preparation during stand-by operation, triplex-piston pump with chrome nickel pump head (hot-water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic I - controls: (start-stop system with switch-off delay, stand-by system for heating, OPH-counter with service information, low-water cut-off), unloader safety-valve c/w Infinitely variable pressure and quantity regulation, separate space for 2x 20l cleaning detergent-container c/w remote activation, 2 different operating control level, 3 robust on-off rotary switches for H.P. pump, heating and detergent, 7,5m connection cable.