



High Pressure Cleaner

KD1140-F

Food progressing
with stainless steel pump, hot water resistant



	1400 U/min	TSS
TOTAL STOP		
		
INOX		

Type		KD1140-F-Standard	KD1140-F-Premium
Voltage	3/PE/AC/50Hz/400V	<ul style="list-style-type: none"> 10m HP-Hose DN08 - 315bar blue Trigger-Gun with swivel Double Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° 35l Cleaning-Detergent tank Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	<ul style="list-style-type: none"> Hose-Reel 15m HP-Hose DN08 - 315bar blue Trigger-Gun with swivel Double Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle Soft Foam Kit with 2l foam detergent tank 25l Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve
Operating pressure	30-180bar/3-18MPa		
Max. pressure	200bar/20MPa		
Discharge capacity	300-1000l/h		
Nozzle size	055		
Max. Inlet temperature	80°C		
Pump speed	1400rpm		
Connected load	6,9kW/10,3A		
Electrical protection	3x16A slow		
Weight net/with package		89kg/113kg	97kg/121kg
Dimensions device/with package (LxWxH)		98x62x100cm/109x63x112cm	98x62x100cm/109x63x112cm

Food progressing with abrasion resistant high pressure hose blue, self-supporting, robust, corrossions free, rotation-moulded device-chassis for food industry, stainless steel, impact-resistant device-cover made of ABS, triplex-piston pump with chrome, nickel plated pump head (hot water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar stainless steel.

Art.No.	551003	551004
----------------	--------	--------