

High Pressure Cleaner

KD1540



| Type | | KD1540-Premium |
|----------------------------------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Voltage | 3/PE/AC/50Hz/400V | <ul style="list-style-type: none"> Hose-Reel 20m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle 25l Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve |
| Operating pressure | 30-280bar/3-28MPa | |
| Max. pressure | 300bar/30MPa | |
| Discharge capacity | 300-1500/h | |
| Nozzle size | 070 | |
| Max. Inlet temperature | 45°C | |
| Pump speed | 1400rpm | |
| Connected load | 13,8kW/24A | |
| Electrical protection | 3x32A slow | |
| Weight net/with package | | |
| Dimensions device/with package (LxWxH) | | 98x62x100cm/109x63x112cm |

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.

| | |
|---------|--------|
| Art.No. | 553004 |
|---------|--------|