

High Pressure Cleaner

KD1140



Type	KD1140-Standard		KD1140-Premium
Voltage	3/PE/AC/50Hz/400V	• 10m HP-Hose DN08 - 315bar	• Hose-Reel
Operating pressure	30-250bar/3-25MPa	• Trigger-Gun with swivel	• 20m HP-Hose DN08 - 315bar
Max. pressure	270bar/27MPa	• Spray-Lance 900mm c/w Vario-Nozzle	• Trigger-Gun with swivel
Discharge capacity	300-1000l/h	• Stainless-Steel Jet-Nozzle 25°	• Spray-Lance 900mm c/w Vario-Nozzle
Nozzle size	045	• 35l Cleaning-Detergent tank	• Stainless-Steel Jet-Nozzle 25°
Max. Inlet temperature	45°C	• Detergent-Supply c/w Low-Pressure Injector and Metering-valve	• Spray-Lance 900mm c/w Rotary-Nozzle
Pump speed	1400rpm		• 25l Water-Storage tank
Connected load	7,4kW/13,1A		• Water-Supply separation acc. DIN EN 1717 class 4
Electrical protection	3x16A slow		• Chemical supply in high-pressure Jet c/w Metering-valve
Weight net/with package		89kg/113kg	97kg/121kg
Dimensions device/with package (LxWxH)		98x62x100cm/109x63x112cm	98x62x100cm/109x63x112cm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.

Art.No.	551005	551006
---------	--------	--------