



HIGH PRESSURE CLEANER | COLD WATER | MOBILE

Series KD2x2

KD523



KD523 Standard
Art. No. 559001



KD523 Premium
Art. No. 559002



EHRLE GmbH
Industriestraße 3
D-89165 Dietenheim



www.ehrle.com



info@ehrle.com



+49 7303 1600-0

SERIES KD2x2

KD523 Standard and Premium

Device features



HIGH PRESSURE GUN

→ With Easy-Press and stainless steel swivel joint



ON/OFF SWITCH

→ Robust rotary switch



HIGH PRESSURE PUMP

- Triplex brass high-pressure pump
- Ceramic piston
- Stainless steel valves
- Crankshaft drive



STEPLESS PRESSURE CONTROL

→ Fully adjustable pressure and flow regulation for every cleaning application



KUPPLUNGSSYSTEM

→ Schnellkupplungssystem Easy-Click aus Edelstahl



ORDERING SYSTEM

→ Hose reel with 15-20m high pressure hose
7.5m electric cable
Storage device for HP lance

KD523 STANDARD AND PREMIUM

Fields of application



Private area



Building sector



Food



Industry



Garage

KD523 Standard and Premium

Technical data



Type	KD523-Standard		KD523-Premium		
Voltage	1/N/PE/AC/50Hz/230V	<ul style="list-style-type: none"> 10m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 700mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	<ul style="list-style-type: none"> Hose-Reel 15m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 700mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle Detergent-Supply c/w Low-Pressure Injector and Metering-valve 		
Operating pressure	30-140bar/3-14MPa				
Max. pressure	160bar/16MPa				
Discharge capacity	300-600l/h				
Nozzle size	043				
Max. Inlet temperature	45°C				
Pump speed	2800rpm				
Connected load	2,9kW/12,5A				
Electrical protection	16A slow				
Weight net/with package		37kg/41kg		44kg/48kg	
Dimensions device/with package (LxWxH)		60x40x86cm/66x42x96cm		60x40x86cm/66x42x96cm	

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable.

Art.No.	559001	559002
---------	--------	--------



3-Piston High-Line Pump with crankshaft, brass pump head, solid ceramic pistons and stainless steel vents ensures maximum service life of the motor-pump unit.



TSS system with overrun delay. During longer breaks in operation, the unit automatically switches to stand-by mode. After opening the shut-off pistol, it is immediately ready for operation again. This extends the pump service life and prevents current peaks in the electrical system.



High-pressure chemical with control valve. The pump sucks in (when the detergent valve is open) detergent at the same time as the water, which can be applied at high pressure as a result.



Machine total shutdown after 20 minutes. If the machine is not used for more than 20 minutes while it is switched on, the machine switches itself off completely. This increases the service life of the machine.



Leakage detection. In the event of a line leakage inside the pressure washer, the hose or the switch gun, the high pressure washer shuts down automatically.



The **QC315 quick coupling system** enables a quick change of different lances, nozzles and other accessories - without the need for additional tools. With anti-twist system and stainless steel.



The EHRLE high pressure cleaner is equipped with slow-running, air-cooled, 4-pole electric motor (**2800 rpm**).



The **hose reel** consists of a stainless steel shaft and a foldable hand crank, which additionally serves to secure the hose reel. max. 40 meter high pressure hose.