

High Pressure Cleaner

KD623



Type	KD623-Standard		KD623-Premium
Voltage	1/N/PE/AC/50Hz/230V	<ul style="list-style-type: none"> 10m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° 17l Cleaning-Detergent tank Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	<ul style="list-style-type: none"> Hose-Reel 15m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle 15l Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve
Operating pressure	30-160bar/3-16MPa		
Max. pressure	180bar/18MPa		
Discharge capacity	300-600l/h		
Nozzle size	035		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	2,9kW/14,2A		
Electrical protection	16A slow		
Weight net/with package		42kg/66kg	48kg/72kg
Dimensions device/with package (LxWxH)		80,5x48,5x95cm/109x63x104cm	80,5x48,5x95cm/109x63x104cm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar.

Art.No.	558001	558002
---------	--------	--------