


High Pressure Cleaner

KD940-F

Food progressing
with stainless steel pump, hot water resistant



	1400 U/min	TSS
TOTAL STOP		
		
INOX		

Type		KD940-F-Standard	KD940-F-Premium
Voltage	3/PE/AC/50Hz/400V	<ul style="list-style-type: none"> 10m HP-Hose DN08 - 315bar blue 	<ul style="list-style-type: none"> Hose-Reel
Operating pressure	30-130bar/3-13MPa	<ul style="list-style-type: none"> Trigger-Gun with swivel 	<ul style="list-style-type: none"> 15m HP-Hose DN08 - 315bar blue
Max. pressure	150bar/15MPa	<ul style="list-style-type: none"> Double Spray-Lance 900mm c/w Nozzle-Protection 	<ul style="list-style-type: none"> Trigger-Gun with swivel
Discharge capacity	300-840l/h	<ul style="list-style-type: none"> Spray-Lance 900mm c/w Vario-Nozzle 	<ul style="list-style-type: none"> Double Spray-Lance 900mm c/w Nozzle-Protection
Nozzle size	060	<ul style="list-style-type: none"> Stainless-Steel Jet-Nozzle 25° 	<ul style="list-style-type: none"> Stainless-Steel Jet-Nozzle 25°
Max. Inlet temperature	80°C	<ul style="list-style-type: none"> 17l Cleaning-Detergent tank 	<ul style="list-style-type: none"> High and low pressure jet nozzle 25°
Pump speed	1400rpm	<ul style="list-style-type: none"> Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	<ul style="list-style-type: none"> Soft Foam Kit with 2l foam detergent tank
Connected load	4,5kW/7A		<ul style="list-style-type: none"> 15l Water-Storage tank
Electrical protection	3x16A slow		<ul style="list-style-type: none"> Water-Supply separation acc. DIN EN 1717 class 4
Weight net/with package		54kg/73kg	58kg/78kg
Dimensions device/with package (LxWxH)		80,5x48,5x95cm/109x63x104cm	80,5x48,5x95cm/109x63x104cm

Food progressing with abrasion resistant high pressure hose blue, self-supporting, robust, corrosion free, rotation-moulded device-chassis for food industry, stainless steel, impact-resistant device-cover made of ABS, triplex-piston pump with chrome, nickel plated pump head (hot water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar stainless steel.

Art.No.	561003	561004
----------------	--------	--------